

# **Safety Data Sheet**

Section 1: Identification of the Substance/Preparation and of the Company/Undertaking

Product Name: Soak Off Gel Polish SDS Prepared: 7/26/2013 SDS Updated: 6/23/2016

Revision: 02

**Product Use:** Cosmetics

Reference: U3

Manufacture: Hand & Nail Harmony Inc 1545 Moonstone Brea, CA 92821

**Emergency Phone Number:** (800) 535-5053 Information Contacts: (714) 773-9758

Product #s: 01027

# Section 2: Hazards Identification

#### **EMERGENCY OVERVIEW**

This information is based on findings from related or similar materials

 Flammable Liquid May be slightly toxic.

May cause moderate skin injury (reddening & swelling).

May cause eye irritation

Potential Health Effects, Signs and Symptoms of Exposure:

Irritating to the eyes, Symptoms of overexposure may include redness, itching, irritation and watering May be irritating to skin in some individuals, especially after prolonged and/or repeated contact Skin

If product is swallowed, may cause nausea, vomiting, and/or diarrhea Inaestion

Inhalation Vapors of this product may be slightly irritating to the nose, throat and other tissue of the respiratory system. Systems of overexposure can include

coughing ,wheezing, nasal congestion, and difficulty breathing.

NOTE: Refer to Section II, Toxicological Information for Details

Section 3:	Composition	n/Information	on Ingredients

INCI NAME	CAS#	EINECS#	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/OSHA	%
DI-HEMA Trimethylhexyl Dicarbamate	41137-60-4 /72869- 86-4	276-957-5	N/E	N/E	Not Listed	30-60
Butyl Acetate	123-86-4	204-658-1	N/E	N/E	Not Listed	5.0-10.0
Ethyl Acetate	141-78-6	205-500-4	N/E	N/E	Not Listed	3.0-10.0
HEMA	868-77-9	212-782-2	N/E	N/E	Not Listed	3.0-10.0
Hydroxypropyl Methacrylate	27813-02-1	248-666-3	N/E	N/E	Not Listed	3.0-10.0
Isobornyl Methacrylate	7534-94-3	231-403-1	N/E	N/E	Not Listed	3.0-10.0
Nitrocellulose	9004-70-0	N/A	N/E	N/E	Not Listed	1.0-3.0
Alcohol Denat	64-17-5	200-578-6	N/E	N/E	Not Listed	1.0-3.0
Trimethyl Pentanyl Diisobutyrate	6846-50-0	229-934-9	N/E	N/E	Not Listed	1.0-3.0
Isopropyl Alcohol	67-63-0	200-661-7	N/E	N/E	Not Listed	1.0-3.0
Triphenyl Phosphate	115-86-6	204-112-2	N/E	N/E	Not Listed	1.0-3.0

N/E - None Established N/DA - No Data Available \* See section 16 N/R - Not Reviewed N/A - Not Applicable

Di-Hema Trimethylhexyl Dicarbamate Hazard Symbol: Xi Risk Phrases: R36/37/38 Safety Phrases: S14, S3/7, S62 Safety Phrases: S2, S26 Hazard Symbol: Xi Risk Phrases: R36/38 R43 **Butyl Acetate** Hazard Symbol: Xi Risk Phrases: R36/38, R43 Safety Phrases: S2, S26 Ethyl Acetate 2-Hydroxy ethyl methacrylate: Safety Phrases: S2, S26, S28 Hazard Symbol: Xi Risk Phrases: R36/38, R43 Hydroxypropyl Methacrylate: Hazard Symbol: Xi Risk Phrases: R36//37/38, R43 Safety Phrases: S26, S36/37

Isobomyl Methacrylate: Hazard Symbol: Xi Risk Phrases: R36/37/38 Safety Phrases: S26,S27,S28,S29,S30,S33,S35,S36

Triphenyl Phosphate Hazard Symbol: N Risk Phrases: R50/53 Safety Phrases: S16/23/25/29/33 Risk Phrases: R11, R36, R67 Safety Phrases: S2, S7, S16, S24/25, S26 Hazard Symbols: Xi. F Isopropyl Alcohol:

See Section 16 for Risk and Safety Phrase Key

#### Section 4: First Aid Measures

First Aid for Eve Splashes are not likely, however, if product gets into the eyes, flush with plenty of water for at least 15 minutes.

If irritation occurs, seek medical attention immediately.

Remove contaminated clothing and wash contact area with soap and water for 15 minutes. First Aid for Skin In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing has stopped, administer First Aid for Inhalation

artificial respiration and seek medical attention.

First Aid for Ingestion If appreciable quantities are swallowed, seek medical attention.

# **Section 5: Fire Fighting Measures**

Flash Point ( °F/ °C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
38°F/ 3.33°C	No Data	No Data

Soak Off Gel Polish Reference: U3 Method:

WARNING: Flammable. Keep away from heat, lit cigarettes, sparks & open flame .Keep containers closed

Extinguishing Media: Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires.

Fire Fighting Instructions: Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering

confined areas where potential for exposure to vapors or products of combustion exists.

#### Section 6: Accidental Release Measures

Spill: Before cleaning any spills or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.

Dike and contain spill with inert material (e.g. sand or earth). Use ONLY non sparking tools for recovery and clean-up. Transfer liquid to containers for recovery or disposal and solid diking material to separated containers for proper disposal. Remove contaminated clothing promptly and wash

affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of

reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. Dispose and report per regulatory requirements if necessary. Please prevent

washings from entering waterways.

#### Section 7: Handling and Storage

Handling: Keep container closed when not in use. Avoid prolong contact with the product. Avoid breathing vapors of this product. Use in a well ventilated location.

Storage: Product is extremely light sensitive. If exposed to natural light, LED, UVA, UVB or UV any light, material will cure very quickly.

Store in a cool, dry place, away from heat and all types of light.

Store away from incompatible materials

Special precautions Keep this materials away from heat, sparks, and open flame. Keep containers tightly closed when not in use.

#### Section 8: Exposure Controls / Personal Protection

Engineering Controls When working with large quantities of product, provide adequate ventilation. Ensure that an eyewash station, sink or washbasin

is available in case of exposure to eyes.

Personal Protective Equipment

General: To identify additional Personal protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance

with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron

boots, or whole body suits. Nitrile rubber is better than PVC.

Eye / Face Protection: Wear chemical splash goggles
Skin Protection: Wear impervious gloves (Neoprene)

Respiratory Protection: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain

limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations

рΗ

Specific Gravity

Viscosity

%Volatile

found in 29 CFR 1910.134 or European Standard EN 149.

Odor & Odor Threshold

# Section 9: Physical and Chemical Properties

Appearance

viscous liquid	character	istic acrylate odor	NA	(H20=1)	): 1.15		N/DA	By Volur	me: <7.0
							1		
Boiling Point/Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure:	Vapor Density	Evaporation Rate	Ignition	Solubility In 1	Water	(20°C)
N/A	N/A	N/A	(mm Hg) @ 20 C:<0.01	No Data	No Data	No Data	Ir	nsoluble	

Flash Point ( °F/ °C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
38°F/ 3.33°C	No Data	No Data

#### Section 10: Stability and Reactivity

Stability Incapability (Material to Avoid):

Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust

and strong bases.

Hazardous Decomposition Products: Hazardous Polymerization:

Fumes produced when heated to May occur --- Uncontrolled polymerization may cause rapid evolution of heat and increased pressure that could

decomposition may include: result in violent rupture of sealed storage vessels or containers.

carbon monoxide, carbon dioxide

Conditions to Avoid:

Normally Stable

Storage>100°F/38°C, exposure to light, loss of dissolved air, loss of polymerization, contamination with incompatible materials

#### Section 11: Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye
No info available	No info available	No info available	No info available	No info available
Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.				

Sensitization	Mutagenicity	Sub-chronic Toxicity
N/DA	N/DA	N/DA

#### Section 12: Ecological Information

Acute Toxicity to Fish

Ecotoxicological Information

140 Information / tvallable	140 information / Wallable	140 Information / Wallable	140 Illiolillation / Wallable	140 IIIIOIIIIalioii / Wallabio
Environmental Stability:				
Ethyl Acetate: removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours.			6.1 hours.	
butyl Acetate: compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours.			nalf-life in water is 6.1 hours.	
Isopropyl Alcohol:	or water, it is apt to volatilize and biodegrade. The estimated half-life in water is 5.4 days, Isopropyl alcohol is not expected to bioconcentrate.			
Chemical Fate Information				
Biodegradability	degradability No Information Available			
Chemical Oxygen Demand	No Information Available			

Acute Toxicity to Algae

Bioconcentration

Toxicity to Sewage Bacteria

To the best of our knowledge, the ecotoxocological and chemical fate properties have not been thoroughly investigated.

Acute Toxicity to Invertebrates

Do not allow to enter drinking water supplies, wastewater, or soil.

#### Section 13: Disposal Considerations

Waste disposal must be in accordance with appropriate Federal, State and local regulations. US. EPA Waste #: D001
Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on on or near the container. Mix with compatible chemical which is less flammable and incinerate. Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements. For EU Member State, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.

#### Section 14: Transport Information

#### DOT (49 CFR -GND)

Excepted Quantity ( 49 CFR -173.4a) ( $\leq$  30 ml) Consumer Commodity, ORM-D ( $\leq$  1.0 L) UN1263 Paint ,3,II (>1.0 L)

#### IATA (AIR):

Excepted Quantity ( Air Shipper 4.1.2) (≤ 30 ml)
Consumer Commodity,9, ID8000 ( ≤ 0.5 L)
UN1263 Paint ,3,II (> 0.5 L)

#### IMDG (OCN):

Excepted Quantity (2008 IMO -3.5.1)) ( $\le$  30 ml) UN1263 Paint ,3,II LTD QTY( $\le$  1.0 L) UN1263 Paint ,3,II (> 1.0 L)

## TDGR (Canadian GND):

Mark Package "Limited Quantity" or "Quantite Limitee" or "LTD QTY" or "Quant Ltee" ( $\leq$  1.0 L) UN1263, Paint related material, 3, II, (>1.0 L)

## ADR/RID (EU):

UN 1263, Paint Related Material,3,II,ADR

# MEXICO (SCT):

UN1263, Pintura,3,II, Cantidad Limitada (≤ 1.0 L)

#### ADGR(AUS):

UN1263, Paint, 3, II LTD QTY (≤ 1.0L)

#### Section 15: Regulatory Information

US Federal Regulations

US Federal Regulations	
Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act:
	NONE
	This product does not contain any Class I or Class 2 ODS
Clean Water Act: Priority Pollutant	This product contains the following Hazardous Substances as defined by the CWA:
	NONE
	This product does not contain any substances that are a Priority Pollutant or Toxic Pollutant under the CWA
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and /or other applications as an indirect food
	additive.
Occupational Safety and Health Act	This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard. Its
	hazards are:
	Immediate (acute) health hazard
	Delayed (chronic) health hazard
	Reactive hazard
RCRA	This product is not considered to be a hazardous waste under RCRA (40 CFR 261)
SARA Reporting Requirements:	SARA 304 (40 CFR Table 302.4)- Butyl Acetate, Ethyl Acetate
SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.
TSCA Section 8(b) Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA pre-manufacture
	notification requirements.
CERCLA Reportable Quantity (RQ):	Butyl Acetate: 2270 kg; 5000 lbs.; Ethyl Acetate: 2270 kg; 5000 lbs.

Soak Off Gel Polish Reference: U3

#### State Regulations

CA Right-to-Know Law:	Ethyl Acetate CAS #141-78-6, Butyl Acetate CAS # 123-86-4,		
California No Significant Risk Rule:	NONE		
MA Right-to-Know Law:	Titanium Oxide CAS # 13463-67-7, Ethyl Acetate CAS #141-78-6, Butyl Acetate CAS # 123-86-4, Nitrocellulose CAS# 9004-70-0, Triphenyl Phosphate CAS# 115-86-6		
NJ Right-to-Know Law:	Titanium Oxide CAS # 13463-67-7, Ethyl Acetate CAS #141-78-6, Butyl Acetate CAS # 123-86-4		
PA Right-to-Know Law:	Titanium Oxide CAS # 13463-67-7, Ethyl Acetate CAS #141-78-6, Butyl Acetate CAS # 123-86-4, Triphenyl Phosphate CAS# 115-86-6		
FL Right-to-Know Law:	Titanium Oxide CAS # 13463-67-7, Ethyl Acetate CAS #141-78-6, Butyl Acetate CAS # 123-86-4		
MN Right-to-Know Law:	Titanium Oxide CAS # 13463-67-7, Ethyl Acetate CAS #141-78-6, Butyl Acetate CAS # 123-86-4, Triphenyl Phosphate CAS# 115-86-6		

International Regulations

CDSL: Canadian Inventory	Hydroxpropyl methacrylate CAS #27813-02-1 is on the DSL List. WHMIS = D2B
,	Hyroxycyclohexyl phenyl ketone CAS# 947-19-3 is on the DSL list. WHMIS - n/da 2-Hydroxyethyl methacrylate CASE# 868-77-9 is on the DSL List. WHMIS - n/da
	Isobornyl Methacrylate CAS# 7534-94-3 is on the DSL list. WHMIS - n/da Titanium Dioxide CAS# 13463-67-7WHMIS- not controlled
	D&C Violet 2/Cl60725 CAS # 81-48 is not on the DSL List. WHMIS = N/DA
	Ethyl Acetate CAS# 141-78-6 is on the DSL list.WHMIS= B2,D2B
	Butyl Acetate CAS # 123-86-4 is on the list. WHMIS + B2, D1B, D2B
	Acrylates Copolymer CAS # 25035-69-2 is on the DSL list.MHMIS= N/DA

# European Community: HNH Base Gel: HAZARD SYMBOLS: Xi irritant, F: Flammable, Xn: Harmful RISK PHRASES: R22: Harmful if swallowed, R36/38/37: Irritating to eyes, respiratory system, and skin, R43: May cause sensitization by skin contact. R10 Flammable, R11 Highly Flammable, R20 Harmful by inhalation R21 Harmful in contact with the skin, R41 Risk of serious damage to eyes, R50 Very toxic to aquatic organisms R53 May cause long term adverse effect in the aquatic environment, R65 Harmful, may cause lung damage R66 Repeated exposure may cause skin dryness or cracking, R67 Vapors may cause drowsiness and dizziness SAFETY PHRASES: S18: Handle and open container with care, S24/25: avoid contact with skin and eyes, S36/37: Wear suitable protective clothing and gloves, S38: in case of insufficient ventilation, wear suitable respiratory equipment. S16: Keep away from sources of ignition-No Smoking, S23: Do no breathe vapor, S29: Do not empty into drains, S33: Take precautionary measures against.

### Section 16: Other Information

EU Classes and Risk / Safety Phrases :

# Hazard Symbols:

Xi - Irritants

F - Flammable substances or preparations

Xn: Harmful

RISK PHRASES: R22: Harmful if swallowed, R36/38/37: Irritating to eyes, respiratory system, and skin, R43: May
 Ray course constitution by skin contact. R10 Elements R11 Highly Elements R20 Harmful by inhalation.

cause sensitization by skin contact. R10 Flammable, R11 Highly Flammable, R20 Harmful by inhalation

R21 Harmful in contact with the skin, R41 Risk of serious damage to eyes, R50 Very toxic to aquatic organisms

R53 May cause long term adverse effect in the aquatic environment, R65 Harmful, may cause lung damage

R66 Repeated exposure may cause skin dryness or cracking, R67 Vapors may cause drowsiness and dizziness

• SAFETY PHRASES: S18: Handle and open container with care, S24/25: avoid contact with skin and eyes, S36/37:

 $We ar suitable \ protective \ clothing \ and \ gloves, \ \textbf{S38:} \ in \ case \ of \ insufficient \ ventilation, \ we ar \ suitable \ respiratory$ 


equipment. **\$16**: Keep away from sources of ignition-No Smoking, **\$23**: Do no breathe vapor,

S2 Keep out of reach of children; S3/7 Keep container tightly closed in a cool place; S26 In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice; S27 Take off immediately all contaminated clothing; S28 After contact with skin, wash immediately with plenty of water; S29 Do not empty into drains;

S30 Never add water to this product; S33 Take precautionary measures against static discharges; S35 This material and its container must be disposed of in a safe way;

S62 If swallowed, do not induce vomiting: seek medical advice immediately and show the container or label



This information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage use or disposal of the product. This SDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the SDS may not be applicable. If there are any problems or concerns understanding this SDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at (1-800-535-5053).