

Safety Data Sheet

Section 1: Identification of the Substance/Preparation and of the Company/Undertaking			
Product Name: ALL THAT JAZZ - Professional Nail Lacquer Chemical Name: Nail Enamel	SDS Prepared: SDS Updated Revision	1/25/2018 N/A 00	
Product Use: Cosmetics Reference: Sheet 29	Supplied by:	All That Jazz Los Angeles, CA	
	Emergency Pho	one Number:	(800) 535-5053
Product Reference #s : 10464	Information Cor	ntacts:	(714) 773-9758

Section 2: Hazards Identification

GHS Label:

DANGER

Harzard Statements H224: Extremely flar

GHS Classifications

Flammable Liquids, Gatergory 2

Physical

H224: Extremely flammable liquid and vapour

H224: Extremely flammable liquid and vapo	ur.
Precautionary Statements	
Prevention	
P210: Keep away from heat/sparks/open fla	mes/hot surfaces No smoking.
P233: Keep container tightly closed.	
P280: Wear protective gloves/protective clo	thing/eve protection/face protection.
Response:	
•	emove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
Storage:	
P403+P233: Store in a well-ventilated place	. Keep container tightly closed.
EMERGENCY OVERVIEW	
PHYSICAL APPEARANCE:	Liquid
IMMEDIATE CONCERNS:	Highly Flammable
POTENTIAL HEALTH EFFECTS EYES:	Mildly to mederately initiating
	Mildly to moderately irritating
SKIN:	Mild skin irritant
SKIN ABSORPTION:	May cause dermatitis by defatting the skin from prolonged contact.
INGESTION:	Causes gastro-intestinal irritation, nausea, vomiting and diarrhea.
INHALATION:	Prolonged inhalation may be harmful
	Can cause drowsiness, headaches, nausea, vomiting and narcosis
	May cause lung irritation
SIGNS AND SYMPTOMS OF OVEREXPOSU	RE
EYES:	Overexposure in eyes may cause redness, itching and watering
SKIN:	Symptons of skin overexposure in some sensitive individuals may include redness, itching and irritation of affected area
SKIN ABSORPTION:	None known
INGESTION:	May cause irritation of the digestive track
INHALATION:	May cause drowsiness, dizziness, headaches and nausea
ACUTE TOXICITY:	
	Mild to moderate initiation to avec oper offected area
Eyes: Skin:	Mild to moderate irritation to eyes near affected area
Inhalation:	Mild to moderate irritation to skin near affected area
innalation:	High concentrations of vapors can cause drowsiness, dizziness, headaches and nausea
CHRONIC EFFECTS:	None known
CARCINOGENICITY:	Not classifiable as a human carcinogen by the IARC
MUTAGENICITY:	This product is not reported to produce mutagenic effects in humans
REPRODUCTIVE TOXICITY	
REPRODUCTIVE EFFECTS:	This produce is not reported to cause reproductive effects in humans
TERATOGENIC EFFECTS:	This product is not reported to produce Teratogenic effects in humans
MEDICAL CONDITIONS AGGRAVATED:	None known
ROUTES OF ENTRY:	Eye contact, Inhalation
TARGET ORGAN STATEMENT:	Eyes, skin and respiratory system
Section 3: Composition/Information	on Ingredients

INCI Name	CAS#	EINECS#	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/OSHA	%
Butyl Acetate	123-86-4	204-658-1	150ppm	150ppm	Not Listed	15.0 - 50.0

Fire Fighting Instructions:	Remove all ignition	n sources. Wear self	-contained breathing apparatus and complete person	ai protective equipr	nent when entering		
		tinguishers, water for					
Extinguishing Media:		le, foam or dry chem					
Method:							
WARNING: Highly Flammable. Keep away	y from heat, and any source	s of ignition. Keep co	ontainers closed				
2417-4°C ESUITA	100			<u> </u>	NU Data	а	
24°F / -4°C Estima	,		No Data		No Data		
Flash Point (°F/	°C)		Flammable Limit (vol%)		Auto-ignition Tempe	erature (vol%)	
Section 5: Fire Fighting Measure	es						
ç		interior of the second s					
First Aid for Ingestion	•		IATE MEDICAL ATTENTION				
First Aid for Inhalation	•	Remove person to fresh air. Seek medical attention					
First Aid for Skin	0 1	Irrigate with copious amount of sterile water. If irritation occurs, seek medical attention immediately. Wash off with propriety remover, wash affected area with soap and water					
First Aid for Eye	Irrigate with copie	us amount of starilo	vator. If irritation accurs, sock medical attention imm	diatoly			
Section 4: First Aid Measures							
I/R - Not Reviewed	N/A - N	ot Applicable					
V/E - None Established		Data Available	* See section 16				
Diacetone Alcohol	Hazard Symbol: >	G	Risk Phrases: R36		Safety Phrases: S2, S24/25		
-Butyl Alcohol	Hazard Symbol: >		Risk Phrases: R10, R22, R37/38, R41, R67		Safety Phrases: S2, S7/9, S13, S26, S37/39, S46		
Propyl Acetate	Hazard Symbols:		Risk Phrases: R11, R36, R66, R67				
riphenyl Phosphate	Hazard Symbol: >		Risk Phrases: R50, 53		Safety Phrases: S60, S61		
sopropyl Alcohol:	Hazard Symbols:		Risk Phrases: R11, R36, R67		Safety Phrases: S2, S7, S1	6, S24/25, S26	
litrocellulose	Hazard Symbol: F	:	Risk Phrases: R11		Safety Phrases: S2, S16, S3		
Ethyl Acetate	Hazard Symbol: F	, Xi	Risk Phrases: R11, R36, R66, R67		Safety Phrases: S2, S16, S2	26, S33	
Butyl Acetate	Hazard Symbol: F	-	Risk Phrases: R10, R66, R67		Safety Phrases: S2, S25		
Diacetone Alcohol	123-42-2	204-626-7	50 ppm	50 ppm	Not Listed	<1.0	
n-Butyl Alcohol	71-36-3	200-751-6	100 ppm	50 ppm	Not Listed	1.0 - 5.0	
Propyl Acetate	109-60-4	203-686-1	200 ppm	200 ppm	Not Listed	1.0 - 5.0	
Triphenyl Phosphate	115-86-6	204-112-2	N/E	N/E	Not Listed	1.0 - 5.0	
Isopropyl Alcohol	67-63-0	200-661-7	400 ppm	200 ppm	Not Listed	5.0 - 15.0	
Nitrocellulose	9004-70-0	N/A	N/E	N/E	Not Listed	5.0 - 15.0	

Section 6: Accidental Release Measures

Spill:	Before cleaning any spills or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.	
	Dike and contain spill with inert material (e.g. sand or earth). Use ONLY non sparking tools for recovery and clean-up. Transfer liquid to containers	
	for recovery or disposal and solid diking material to separated containers for proper disposal. Remove contaminated clothing promptly and wash	
	affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.	
	US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of	
	reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations	
	require the consultation of Directive 98/24/EC. Dispose and report per regulatory requirements if necessary. Please prevent	
	washings from entering waterways.	

confined areas where potential for exposure to vapors or products of combustion exists.

Section 7: Handling and Storage

Handling:	No smoking Prevent static discharges Exposure by inhalation or skin contact should be minimized by good industrial hygiene Vapor is heavier than air, spreads along the ground. Vapor can form an explosive mixture in air, prevalent in empty unclear vessels Use non-sparking utensils when handling this material
Storage:	Keep containers tightly closed when not in use. Store in a cool, dry place, away from heat and all types of light. Eliminate possible point ignition sources, e.g. No smoking, Naked flames, static discharges Use flame proof electrical equipment.
Special precautions	Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handle with care
Section 8: Exposure Controls / Perso	nal Protection
Engineering Controls Personal Protective Equipment General:	When working with large quantities of product, provide adequate ventilation. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. No special body protection is required under typical circumstances of use and handling. If necessary refer to appropriate standards of Canada, The E.C members states, or U.S. OHSA.

Eye / Face Protection:	Depending on the use of this product, splash or safety glasses may be worn.
Skin Protection:	If anticipated that prolonged and repeated skin contact will occur during use of this product, wear latex or gloves for routine industrial use.
Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. If necessary, use respiratory protection.

Section 9: Physical and Chemical Properties

Appearance	Odor & Odor Threshold	pH	Specific Gravity	Viscositv	Vapor Density
Appearance		рн	Specific Gravity	VISCOSILY	vapor Density
viscous liquid, various colors	characteristic acrylate odor	NA	(H20=1): 0.97 - 1.10	N/DA	Heavier than air

Boiling Point/Freezing Point	Decomposition Temperature N/A	Partitioning Coefficient Log Po/w N/A	Vapor Pressure:	Evaporation Rate	Ignition No Data	Solubility In Water (20°C)
Flash Point (°F/ °C)			Flammable Limit (vol%) Auto-ignition Temperature (vol%)		rature (vol%)	

Section 10: Stability and Reactivity

Stability:	Incapability (Material to Avoid):		
Stable under ambient conditions when stored properly.	Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust		
	and strong bases.		
and a substantial birth terms and uses the super-duct of the super-	Hazardous Polymerization: May occur, if exposed to extremely high temperatures.		
Conditions to Avoid:			

This product is incompatible with strong oxidizers, strong acids, or strong bases.

Section 11: Toxicological Information

This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the product, which are found in scientific literature. This data has not been represented in

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin/eyes
No info available	No info available	No info available	No info available

Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.

Suspected Carcinogen	Mutagenicity	Sub-chronic Toxicity
No info available	This product is not reported to produce mutagenic effects in humans	No info available

Section 12: Ecological Information

Ecotoxicological Information

Acute Toxicity to aquatic life	Acute Toxicity to plants and animals	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
No Information Available	No Information Available	No Information Available	No Information Available	No Information Available

Environmental Stability:

The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows

Ethyl Acetate:	Koc= 0.73. Water Solubility: 64,000 mg/l. Bioconcentration Factor= 4-14. Biocincentration is not anticipated to be significant. This compound can be remo from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours.	
Butyl Acetate:	Koc= 1.8. Water Solubility: 120 Parts H2O at 25°C (77°F). Bioconcentration Factor= 4-14. Biocincentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours.	
Isopropyl Alcohol:	Low Kow= 0.05-0.14. Isopropyl alcohol occurs naturally; it is generated during microbial degradation pf plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated half-life in water is 5.4 days, Isopropyl alcohol is not expected to bioconcentrate.	
Chemical Fate Information		
Biodegradability	No Information Available	
Chemical Oxygen Demand	No Information Available	

To the best of our knowledge, the ecotoxocological and chemical fate properties have not been thoroughly investigated. Do not allow to enter drinking water supplies, wastewater, or soil.

Section 13: Disposal Considerations

Waste disposal must be in accordance with appropriate Federal, State and local regulations.

Section 14: Transport Information

DOT (49 CFR -GND)

Excepted Quantity (49 CFR -173.4a) (≤ 30 ml) Consumer Commodity, ORM-D (≤ 1.0 L) UN1263 Paint ,3,II (>1.0 L)

IATA (AIR):

 $\label{eq:constraint} \begin{array}{l} \mbox{Excepted Quantity (Air Shipper 4.1.2) (≤30 ml)} \\ \mbox{Consumer Commodity,9, ID8000 (≤0.5 L)} \\ \mbox{UN1263 Paint ,3,II (>0.5 L)} \end{array}$

IMDG (OCN):

 $\begin{array}{l} \mbox{Excepted Quantity (2008 IMO -3.5.1)) (\leq 30 \mbox{ ml}) \\ \mbox{UN1263 Paint ,3,II LTD QTY(\leq 1.0 L) } \\ \mbox{UN1263 Paint ,3,II (> 1.0 L) } \end{array}$

TDGR (Canadian GND):

Mark Package "Limited Quantity" or "Quantite Limitee" or "LTD QTY" or "Quant Ltee" (\leq 1.0 L) UN1263, Paint related material, 3, II, (>1.0 L)

ADR/RID (EU):

MEXICO (SCT):

UN1263, Pintura,3,II, Cantidad Limitada (≤ 1.0 L)

ADGR(AUS):

UN1263, Paint, 3, II LTD QTY (≤ 1.0L)

Section 15: Regulatory Information

US Federal Regulations	
Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act:
	NONE
	This product does not contain any Class I or Class 2 ODS
Clean Water Act: Priority Pollutant	This product contains the following Hazardous Substances as defined by the CWA:
	NONE
	This product does not contain any substances that are a Priority Pollutant or Toxic Pollutant under the CWA
FDA:	This product complies with the appropriated sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics)
SARA Reporting Requirements:	SARA 304 (40 CFR Table 302.4)- Butyl Acetate, Ethyl Acetate
SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.
TSCA Inventory Status:	This product contains chemicals listed on the TSCA inventory
CERCLA Reportable Quantity (RQ):	Butyl Acetate: 5000 lbs.; Ethyl Acetate: 5000 lbs.

State Regulations:

Ingredients in this mixture are found on the following state criteria list:

CA Right-to-Know Law:	Ethyl Acetate, Butyl Acetate, Isopropyl Alcohol	
Delaware Air Quality Management List	Ethyl Acetate, Butyl Acetate, Nitrocellulose	
Massachusetts Hazardous Substances List	Ethyl Acetate, Butyl Acetate, Nitrocellulose, Isopropyl Alcohol	
Minnesota Hazardous Substances List	Ethyl Acetate, Butyl Acetate, Isopropyl Alcohol	
NJ Right-to-Know Law:	Isopropyl Alcohol	

New York List of Hazardous Substances	Ethyl Acetate, Butyl Acetate
PA Right-to-Know Law:	Ethyl Acetate, Butyl Acetate, Isopropyl Alcohol
Washington Permissible Exposure Limits for Air Contaminants	Ethyl Acetate, Butyl Acetate, Isopropyl Alcohol
Wisconsin Hazardous Substances List	Ethyl Acetate

International Regulations:

Canadian Regulations:

Ethyl Acetate CAS# 141-78-6 is on the DSL list.WHMIS= B2,D2B

Butyl Acetate CAS # 123-86-4 is on the list. WHMIS + B2, D1B, D2B

This product has been classify according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL.

None of the components of this product are listed on the Priorities substances List. Class B Flammable Liquid.

Section 16: Other Information

67/548/EU Requirements:

European Community:

The primary component of this product is listed in Annex I of the EU Directive 67/548/EEC



 HAZARDOUS SYMBOLS: Xi - Irritants F - Highly Flammable

Xn- Harmful • **RISK PHRASES:** R10 Flammable

R11 Highly Flammable

R22 Harmful if swallowed

R36 Irritating to eyes

R37/38 Irritating to respiratory system and skin

R41 Risk of serious damage to eyes

R50 Very toxic to aquatic organisms

R53 May cause long-term adverse effects in the aquatic environment

R66 Repeated exposure may cause skin dryness or cracking

R67 Vapors may cause drowsiness and dizziness

• SAFETY PHRASES:

S2 Keep out of reach of children

S7/9 Keep container tightly closed and in a well-ventilated place

S13 Keep away from food, drink and animal foodstuffs

S16 Keep away from sources of ignition-No Smoking,

S24/25 Avoid contact with skin and eyes

S25 Avoid contact with eyes

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S29: Do not empty into drains


S33 Take precautionary measures against static discharges

S37/39 Wear suitable gloves and eye/face protection

S46 If swallowed, seek medical advice immediately and show this container or label

S60 This material and its container must be disposed of as hazardous waste.

S61 Avoid release to the enivronment. Refer to special instructions/Safety data sheets.



This information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage use or disposal of the product. This SDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the SDS may not be applicable. If there are any problems or concerns understanding this SDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at (1-800-535-5053).