

Safety Data Sheet

Section 1: Identification of the Substance/Preparation and of the Company/Undertaking

Product Name: Matte Top It Off SDS Prepared: 3/18/2014
SDS Updated: 3/31/2015

Revision: 01

Product Use: Cosmetic

Manufacture: Hand & Nail Harmony

1545 Moonstone, Brea, CA 92821

 Product #:
 Emergency Phone Number:
 (800) 535-5053

 01222
 Information Contacts:
 (714) 773-9758

Section 2: Hazards Identification

EMERGENCY OVERVIEW

This information is based on findings from related or similar materials.

May be slightly toxic.

May cause moderate skin injury (reddening & swelling).

May cause eye irritation



Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry No specific information available.

Eye Contains materials that are essentially nonirritating, but contact may cause slight transient irritation.

Skin Contains materials that may cause moderate skin injury (reddening and swelling) and/or sensitization.

Prolonged contact may cause blister formation (burns). Since irritation may not occur immediately, contact can go unnoticed.

Ingestion No specific information available.

Inhalation No specific information available. Low volatility makes vapor inhalation unlikely

NOTE: Refer to Section II, Toxicological Information for Details

Section 3: Composition/Information on Ingredients						
INCI NAME	CAS#	EINECS#	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/OSHA	%
Di-HEMA trimethylhexyl dicarbamate	72869-86-4	276-957-5	N/E	N/E	Not Listed	25.0 - 50.0
HEMA	868-77-9	212-782-2	N/E	N/E	Not Listed	25.0 - 50.0
Trimethylolpropane Trimethacrylate	150-76-5	205-769-8	N/E	N/E	Not Listed	5.0 - 10.0

N/E - None Established N/DA - No Data Available * See section 16

N/R - Not Reviewed N/A - Not Applicable

Di-Hema trimethylhexyl dicarbamate Hazard Symbol: Xi Risk Phrases: R36/37/38 Safety Phrases: S14, S3/7, S62
HEMA Hazard Symbol: Xi Risk Phrases: R36/38, R43 Safety Phrases: S2, S26,, S28

Trimethylolpropane Trimethacrylate Hazard Symbol: Xi Risk Phrases: R11, R36//37/38 Safety Phrases: S26

See Section 15 for Risk and Safety Phrase Key

Section 4: First Aid Measures

First Aid for Eye Flush with plenty of water for 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention

First Aid for Skin Remove contaminated clothing and wash contact area with soap and water for 15 minutes.

Wash clothing before reuse.

First Aid for Inhalation In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing has stopped, administer

artificial respiration and seek medical attention.

Section 5: Fire Fighting Measures

Flash Poin	Flash Point (°F/ °C) Flamma		Auto-ignition Temperature (vol%)		
> 212°F/100°C Setaflash		No Data	No Data		
Method:	Method:				
Extinguishing Media:	Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires.				
Fire Fighting Instructions:	Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering				
	confined areas where potential for exposure to vapors or products of combustion exists.				

Unusual Hazards:

High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessels or containers. Avoid the use of a stream of water to control fires since frothing can occur.

Section 6: Accidental Release Measures

Spill or Release Producers:

Spontaneous polymerization can occur. Although material in non-flammable please try to eliminate ignition sources.

Use eye and skin protection. Place leaking containers in a well ventilated area.

Dike and recover large spills. Soak up small spills with inert solids (such as vermiculite, clay) and sweep/shovel into disposal container. Wash spill area with strong detergent and water solution; rinse with water, but minimize water use during clean-up. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. Dispose and report per regulatory requirements if necessary. Please prevent washings from entering waterways.

Section 7: Handling and Storage

Handling:

Avoid contact with skin and eyes. Avoid breathing vapor. Keep container closed when not in use. Avoid prolonged exposure to light. Remove all contaminated clothing, shoes, belts and other leather goods immediately. Incinerate leather goods (including shoes). Wash contaminated clothing thoroughly before reuse. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential.

Most acrylic monomers have low viscosities, thus only needing room temperature conditions to facilitate proper pouring techniques. However, viscous type gels such as these may require heating to facilitate proper pouring techniques. To ensure that this happens product may be heated to 60°C/140°F for not more than 24 hours. Do NOT use localized heat sources such as band heaters to heat/melt product. Do NOT use steam. Hot boxes or hot rooms are recommended for heating/melting material. The hot box and/or room should only be set to a maximum temperature of 60°C/140F. Do not overheat, this may compromise product effectiveness and should be avoided. Refrain from multiple reheating of product, this will also diminishing the quality of the product.

Storage:

Product is extremely light sensitive. If exposed to natural light, LED, UVA, UVB or UV any light, material will cure very quickly. Store in a cool, dry place, away from heat and all types of light. Store at temperatures below 100°F/38°C but above the product's freezing point. If no freezing point is given, keep above 32°F/0°C at all times.

Explosion Hazard:

High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessels or containers.

Section 8: Exposure Controls / Personal Protection

Engineering Controls

Local exhaust recommended to control exposure which may result from operations generating aerosols and hot operations generating vapors.

Personal Protective Equipment

General:

To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard En166 be conducted before using this product. Provide eye stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.

Eye / Face Protection:

Wear safety splash goggles.

Skin Protection:

Wear impervious gloves (Neoprene)

Respiratory Protection:

A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN149.

Section 9: Physical and Chemical Properties

Appearance	Odor & Odor Threshold	pН	Specific Gravity	Viscosity	%Volatile
Clear slight violet, semi-viscous liquid	characteristic acrylate odor	NA	(H20=1): 1.15	N/DA	By Volume: <0.5

	Boiling Point/Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure:	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)
ſ				(mm Hg) @				
ı	N/A	N/A	N/A	20 C:<0.01	No Data	No Data	No Data	Insoluble

Flash Point (°F/ °C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
212°F/100°C Penske-Martin	No Data	No Data

Section 10: Stability and Reactivity

Stability Incapability (Material to Avoid):

Normally Stable Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust

and strong bases.

Hazardous Decomposition Products: Hazardous Polymerization:

Fumes produced when heated to May occur --- Uncontrolled polymerization may cause rapid evolution of heat and increased pressure that could

decomposition may include: result in violent rupture of sealed storage vessels or containers.

carbon monoxide, carbon dioxide Conditions to Avoid:

Storage>100°F/38°C, exposure to light, loss of dissolved air, loss of polymerization, contamination with incompatible materials.

Section 11: Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye	
No info available	No info available	No info available	No info available	No info available	
Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.					

Sensitization	Mutagenicity	Sub-chronic Toxicity
No Information Available	No Information Available	No Information Available

Section 12: Ecological Information

Ecotoxicological Information

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
No Information Available	No Information Available	No Information Available	No Information Available	No Information Available

Chemical Fate Information

Biodegradability	No Information Available
Chemical Oxygen Demand	No Information Available

To the best of our knowledge, the ecotoxocological and chemical fate properties have not been thoroughly investigated.

Do not allow to enter drinking water supplies, wastewater, or soil.

Section 13: Disposal Considerations

Non-contaminated, properly inhibited product is not a RCRA hazardous waste. It is the generators responsibility to determine what is classified as a hazardous waste. Comply with all federal, state, and local regulations. Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

Section 14: Transport Information

DOT (49 CFR 172)

Proper Shipping Name: Non-Regulated Material

 Identification Number:
 N/A

 Marine Pollutant:
 No

 Special Provisions:
 N/A

 Emergency Response Guidebook (ERG) #:
 N/A

IATA (DGR):
Proper Shipping Nam

Proper Shipping Name: Non-Regulated Material

Class or Division: N/A
UN or ID Number: N/A
Packaging Instructions:

Emergency Response Guidance (ICAO)#:

IMO (IMDG):

Proper Shipping Name: Non-Regulated Material

Class or Division: N/A
UN or ID Number: N/A
Special Provisions & Stowage/Segregation: None

Emergency Schedule (EmS)#:

Other Information: Flash point >100 °C

Section 15: Regulatory Information

			_		
บร	red	erai	Rec	ıula	tions

OO I CUCIAI NEGUIATIONS				
Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act: • NONE			
	This product does not contain ODS's			
	This product does not contain ODO's			
Clean Water Act: Priority Pollutant	This product contains the following Hazardous Substances as defined by the CWA:			
	NONE			
	This product does not contain any substances that are a Priority Pollutant or Toxic Pollutant under the CWA			
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and /or other applications as an indirect food			
	additive.			
Occupational Safety and Health Act	This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard. Its			
	hazards are:			
	Immediate (acute) health hazard			
	Delayed (chronic) health hazard			
	Reactive hazard			
RCRA	This product is not considered to be a hazardous waste under RCRA (40 CFR 261) RCRA Code:			
SARA Title III: Section 302 (TPQ)	This product contains no chemicals regulated under Sec. 302 as extremely hazardous substances that carry a TPQ.			
SARA Title III: Section 302 (RQ)	This product contains no chemicals regulated under Section 304 as extremely hazardous chemicals for emergency			
	release notification ("CERCLA" List):			
SARA Title III: Section 311-312:	This product is considered hazardous under the OSHA Hazard Communication Standard and is regulated under			
	Section 311-312 (40 CFR 370). Its hazards are:			
	Immediate (acute) health hazard			
	Delayed (chronic) health hazard			
	Reactive hazard			
SARA Title III: Section 313:	This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the			
	Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:			
	• NONE			
TSCA Section 8(b) Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture			
	notification requirements.			
TSCA Significant New Use Rule:	None of the chemicals in this material have a SNUR under TSCA.			

State Regulations

State Regulations		
CA Right-to-Know Law:	NONE	
California No Significant Risk Rule:	NONE	
MA Right-to-Know Law:	NONE	
NJ Right-to-Know Law:	NONE	
PA Right-to-Know Law:	NONE	
FL Right-to-Know Law:	NONE	
MN Right-to-Know Law:	NONE	

International Regulations

2-hydroxyethyl Methacrylate CAS # 868-77-9 is on the DSL list. WHMIS = n/da
Trimethylolpropane Trimethacrylate Esters CAS# 3290-92-4 is on the DSL list .WHMIS = n/da

Section 16: Other Information

Labeling according to EC Directives - 1999/45/EC

European Community:



HNH Base Gel:

- HAZARD SYMBOLS: Xi irritant,
- RISK PHRASES: R22: Harmful if swallowed, R36/38: Irritating to eyes, respiratory system, and skin, R43: May cause sensitization by skin contact.
- SAFETY PHRASES: \$18: Handle and open container with care, \$24/25: avoid contact with skin and eyes, \$36/37: Wear suitable protective clothing and gloves, \$38: in case of insufficient ventilation, wear suitable respiratory equipment.

EU Classes and Risk / Safety Phrases for Referenced Ingredients (See Section 2):

Hazard Symbols:

Xi - Irritants

Risk Phrases:

R36/37/38 Irritating to eyes, respiratory system and skin; R43 May cause sensitization by skin contact

Safety Phrases:

S2 Keep out of the reach of children;

S3/7 Keep container tightly closed in a cool place;


S26:In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S28:After contact with skin, wash immediately with plenty of water.

S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Section 16: Other Information

Hazard Rating System (Pictograms)



This information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If there are any problems or concerns understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at (1-800-535-5053).